







1	2	3	4	5	6	7	8
A						REV.	Q'TY
B						ECN. NO.	APR.
C						FIRST RELEASE	Jason 2018.03.29




PIN	NO.	Dim A	Dim B
2	WF13-0N02F18N11	1.25	7.65
3	WF13-0N03F18N11	2.50	8.90
4	WF13-0N04F18N11	3.75	10.15
5	WF13-0N05F18N11	5.00	11.30
6	WF13-0N06F18N11	6.25	12.65
7	WF13-0N07F18N11	7.50	13.90
8	WF13-0N08F18N11	8.75	15.15
9	WF13-0N09F18N11	10.00	16.40
10	WF13-0N10F18N11	11.25	17.65
11	WF13-0N11F18N11	12.50	18.90
12	WF13-0N12F18N11	13.75	20.15
13	WF13-0N13F18N11	15.00	21.40
14	WF13-0N14F18N11	16.25	22.65
15	WF13-0N15F18N11	17.50	23.90
20	WF13-0N20F18N11	23.75	30.15
30	WF13-0N30F18N11	36.25	42.65







NOTES:

1. Working temp: -25°C ~ 85°C.
2. Voltage rating: 50V AC/DC(rms)
3. Contact resistance: 40mΩ max.
4. Insulation resistance: 100MΩ min.
5. Current rating: 1A AV/DC
6. Withstanding Voltage: 500V AC/minute
7. Pin Retention Force: 0.5N min.
8. Housing material: PA9T UL94-V0, Natural
9. Terminal materl: Brass, plating Ni 40μ" min , plating Au 0.8μ"min.
10. Solder tab material: Brass, plating Ni 40μ" min , plating Au 0.8μ"min.



DIMENSION IN mm		山谷道	深圳市山谷道电子有限公司
TOLERANCE UNLESS OTHERWISE SPECIFIED			
.X±0.35	X.*± 5°	APR.	Alex
.XX±0.25	.X*± 3°	CHK.	Jack
.XXX±0.15	.XX*± 1°	DRA.	Jave
SIZE A4	SCALE 4:1	SHEET 1 / 2	REV. A

1	2	3	4	5	6	7	8
A						A	
					PRELIMINARY DESIGN IS SUBJECT TO CHANGE WITHOUT PRIOR NOTICE		
					A	FIRST RELEASE	Jason 2018.03.29



NOTE:

- 1.10 SPROCKET HOLE PITCH CUMULATIVE TOLERANCE ±0.2mm.
2. CARRIER CAMBER NOT TO EXCEED 1mm IN 100mm.
3. ALL DIMENSIONS MEET EIA-481 REQUIREMENTS.
4. MATERIAL: CLEAR ANTISTATIC PS, COLD SEALING.
5. COMPONENT LOAD PER REEL: 2000 PCS.

PIN	NO.	Dim C	Dim W	PCS/RELL	RELL/CARTON	PCS/CARTON
2	WF13-0N02F18N11	7.50	16.00	2000	12	24000
3	WF13-0N03F18N11					
4	WF13-0N04F18N11	11.50	24.00	10	20000	
5	WF13-0N05F18N11					
6	WF13-0N06F18N11					
7	WF13-0N07F18N11					
8	WF13-0N08F18N11					
9	WF13-0N09F18N11					

DIMENSION IN mm		山谷道	深圳市山谷道电子有限公司		
TOLERANCE UNLESS OTHERWISE SPECIFIED					
.X±0.35	X±5°	APR.	TITLE: WAFER PH1.25mm H1.85mm 90°SMT		
.XX±0.25	X±3°	CHK.	DWG NO. WF13-0NxxF18N11		
.XXX±0.15	XX±1°	DRA. Jave	PROJ.	CUSTOMER DRAWING	
SIZE A4	SCALE NA	SHEET 2/2	REV. A		